Technical Specifications

HP Series 3 Pro FHD Monitor- 324pf



Front

1. Power Button

2. Power LED

Technical Specifications

HP Series 3 Pro FHD Monitor- 324pf



- 1. Joypad OSD button
- 2. Security Cable Slot
- 3. Power Connector

Back

- 4. DisplayPort™ 1.2
- **5.** HDMI 1.4 Port
- 6. VGA Port

Technical Specifications

Model: 9U5J5UT

Panel SpecificationsDisplay Size (Diagonal)60.5 cm (23.8")Viewable Diagonal Size60.47 cm (23.8")

Panel Technology IPS
Curvature Flat
Max Refresh Rate 100 Hz

Native ResolutionFHD (1920 x 1080)Panel Bit Depth8 bit (6 bit + FRC)

Aspect Ratio 16:9
Brightness (Typical) 250 nits
Display Contrast Ratio (Static) 1000:1
Display Contrast Ratio (Dynamic) 8M:1

Flicker FreeYes (TÜV certified)Pixel Pitch0.2745 x 0.2745 mm

Pixels Per Inch (PPI) 93 PPI

Display ColorsUp to 16.7 million colors supported*
*Number of colors thru A-FRC technology.

30,000 hours

Backlight Lamp Life Minimum

(To Half Brightness - In Hours)

Blacklight Type Edge-lit, WLED Screen Treatment Anti-glare

Hardness 3H Haze 25%

Response Time (Typical) 5ms GtG (with overdrive)

Horizontal Viewing Angle
(Typical Cr>10)

Vertical Viewing Angle (Typical Cr>10)

178°

Panel Active Area Metric (W X H) 52.7 x 29.64 cm Panel Active Area Imperial (W X H) 20.75 x 11.67 in

NOTE: Performance specifications represent the typical specifications provided by HP's component

manufacturers; actual performance may vary either higher or lower.

Color NTSE 72%

Color Management Color Space RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2

RGB Channel Adjust Yes. Gain

Default Color Temperature Standard (6500K)

Monitor Specifications Bezel Type 3-sided borderless

Color Of StandBlackColor Of HeadBlackTilt-5 to +23°

Vesa Mounting 100 mm x 100 mm

Security Lock Standard Security Lock Slot

Detachable Stand Yes

Warranty 3/3/0 for LA, NA, EMEA, APJ (3/3/3 in select APJ Countries)



Technical Specifications

Low Blue Light

Management Software

Yes, HP Eve Ease (TÜV Low Blue Light Hardware Solution)

certified)

HP Client Management Script Library (CMSL)*

HP Display Center**

* The Client Management Script Library must be downloaded to the connected PC to run CMSL commands. Some limitations may apply to legacy displays. Visit support.hp.com to download HP

CMSL.

** Host PC requires Windows 10 and above. HP Display Center is

available on the Microsoft store.

On Screen Display (OSD)

On Screen Display

Native Resolution

Brightness+, Image, Color, Input, Power, Menu,

Management, Information, Exit

FHD (1920 x 1080)

* DisplayPort™ 1.2 or HDMI 1.4 required to drive panel at its

native resolution.

The video card of the connected PC must be capable of

supporting 1920x1080at 100 Hz with 8-bit color using one HDMI or DisplayPort™: 1920x1080 at 60 Hz with 8-bit color using one

Maximum Resolution

Preset Graphic Modes/Supported

Resolutions

Languages

FHD (1920 x 1080 @ 100 Hz)

640 x 480 @ 60Hz

640x480@75Hz (Digital inputs only)

720 x 400 @ 70 Hz 800 x 600 @ 60 Hz

800x600 @ 75Hz (Digital inputs only)

1024 x 768 @ 60 Hz

1024 x 768 @ 75 Hz (Digital inputs only)

1280 x 720 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 1024 @ 60 Hz

1280 x 1024 @ 75 Hz (Digital inputs only)

1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1680 x 1050 @ 60Hz

1920x1080 @ 50Hz (Digital inputs only)

1920 x 1080 @ 60Hz

1920x1080 @ 75Hz (Digital inputs only) 1920x1080 @ 100z (Digital inputs only)

Minimum Vertical Scan Rate

Maximum Vertical Scan Rate VGA 60 Hz, HDMI & DisplayPort™ 100 Hz 30 kHz

Minimum Horizontal Scan Rate

Maximum Horizontal Scan Rate HDMI & DisplayPort™: 115 kHz, VGA:80 kHz HDMI & DisplayPort™:300MHz, VGA:170MHz **Maximum Pixel Clock**

User Programmable Modes Yes, VGA 11, HDMI / DisplayPort™ 18

User-Assignable Function Buttons Yes, 4 (VGA: 6 options, HDMI / DisplayPort™: 5 options)

11 (English, Spanish, German, French, Italian,

Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese

and Russian)



Technical Specifications

Connector Types DisplayPort™ 1 DisplayPort™ 1.2

> HDMI 1 HDMI 1.4

HDCP Yes, DisplayPort™ and HDMI

VGA 1 VGA

Special Features Switch Monitor Power button

> Next Active Input / Up button Brightness / Down button Information / Left button Color / Right button Menu / Enter button

User Presets 11(VGA)/18(HDMI & DisplayPort™)

Power & Operating Power Supply Internal

Specs

Power Source 100 - 240 VAC 50/60 Hz

Power Consumption- Max 30 W **Energy Saving/Stand By Mode** 0.5 W **Power Consumption - Typical** 20 W

Energy Star Data Operational Mode at 100 VAC 13.96 W Operational Mode at 115 VAC 13.96 W

Operational Mode at 230 VAC 13.96 W

EU Energy Efficiency On-mode Power Consumption for 14 W Class (ErP LOT-5) **Standard Dynamic Range (SDR)**

EU Energy Efficiency ErP LOT5 Energy Efficiency Class for Class (ErP LOT-5) Standard Dynamic Range (SDR)

Operating Conditions Operating Temperature - Celsius

Operating Temperature - Fahrenheit 41-95°F Non-Operating Temperature - Celsius -40 - 65°C

Non-Operating Temperature -

Fahrenheit Operating Humidity 20 – 80% Relative Humidity (non-condensing)

5~35°C

-40 - 149°F

Non-Operating Humidity 5~95%RH

0~5,000m (16,400 ft.) **Operating Altitude Metric** Non-operating Altitude Metric 0~12,192m (40,000 ft.)

Operating Altitude Imperial 0~16.400ft Non-operating Altitude Imperial 0~40,000ft

Certifications and Low Halogen Yes **Compliances**

> **Agency Approvals and Certifications** WW application

> > UAE/EUP Lot6 and Lot26/ Eup Lot5/ Energy Star / TCO Edge/ TCO / Australia MEPS/ Vietnam MEPS/ CEC/ Bauart/ China CCC/ cTUVus/ Korea KC/ Korea KCC/ Korea e-Standby/ CB(62368-1&60950)/ ISO9241-307/ CE/FCC/VCCI/RCM/C-TICK/IC/ India BIS/ Taiwan BSMI/ Mexico NOM/ South Africa Energy Efficiency/ Argentina S-

Technical Specifications

Mark/ Singapore PSB/ Cambodia ISC/ EAC//Mexico Energy /CEL/Ukraine(DOC&COC)/NRCS/Ukraine energy/PSE/SEPA/TGM / Works with Chromebook *

* This product works with devices capable of running the latest version of ChromeOS and has been certified to meet Google's compatibility standards. Google is not responsible for the operation of this product or its compliance with safety requirements. Chromebook and the Works With Chromebook badge are trademarks of Google LLC.



Microsoft WHQL Certification ENERGY STAR® Certified EPEAT® Registered

Regions need to verify by country

Windows 11, Windows 10

Yes

EPEAT® Gold in United States*

*Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit www.epeat.net for more information.

China Energy LabelCEL Grade 2TCO Certified EdgeYesTCO CertifiedYes

SmartWay Transport Partnership - NA only

Yes (NA sku)

Contains Recycled Plastics

Contains Recycled Plastics

85% ITE-derived closed loop plastic*

*ITE Derived Closed Loop Plastic percentage is based on the definition set in the IEEE 1680.1-2018 standard.

Recyclable Packaging (Box, packing materials)

Outside Box is 100% sustainably sourced and recyclable*

Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable**

- * 100% outer box packaging is made from sustainably sourced certified and recycled fibers.
- ** Molded pulp cushions are made from 100% recycled wood fiber and organic materials.

| Unit Product/Package |
|----------------------|
| Specifications |

Product Dimensions
(Unpacked with stand) (W x D x H)
Product Dimensions
(Packed) (W x D x H)
Display Head Dimensions
(Unpacked without stand) (W x D x H)

Base Area Footprint
(w x d mm)

Bezel Measurements

 Metric
 Imperial

 53.89 x 18.05 x 39.79 cm
 21.22 x 7.11 x 15.67 in

 59.5 x 12.4 x 39.1 cm
 23.43 x 4.88 x 15.39 in

 53.89 x 5.14 x 32.36 cm
 21.22 x 2.02 x 12.74 in

 174 x 170 mm
 6.85 x 6.69 in

 Top: 1.4 cm
 Top: 0.05 in

Sides: 1.4 cm

Sides: 0.05 in

Technical Specifications

Bottom: 20.2 cm Bottom: 0.79 in **Product Weight** 8.3 lb 3.77 kg

(Unpacked with stand)

Product Weight 5.86 kg 12.92 lb

(Packed)

Product Weight 7.45 lb 3.38 kg

(Head Only)

Pallet Information Pallet Dimensions Slip Sheet: 1200x1002x1980 mm Slip Sheet:

> (20 ft &40 ft) (L x W x H mm)

Slip Sheet: 1200 x 1002 x 2374

mm (40 ft HQ)

Pallet: 1200x1002 x 2100 mm (20

ft & 40 ft)

Pallet: 1200 x 1002 x 2494 mm

(40 ft HQ)

82.68 inch (20 ft &

40 ft)

Pallet: 47.24 x 39.45 x 98.19 inch (40 ft

Slip Sheet: 992.08 lb

47.24x39.45x77.95

inch (20 ft &40 ft)

Slip Sheet: 47.24 x

39.45 x 93.46 inch

Pallet: 47.24x39.45x

(40 ft HQ)

Pallet Total Weight Slip Sheet: 450 kg (20 ft & 40 ft)

Slip Sheet: 535 kg (40 ft HQ) Pallet: 460kg (20 ft & 40 ft) Pallet: 550 kg (40 ft HQ)

(20 ft & 40 ft) Slip Sheet: 1177 lb (40 ft HQ)

Pallet: 1014.13 lb (20 ft & 40 ft) Pallet: 1210 lb (40 ft

HO)

5 (20ft/40ft slip sheet & pallet) **Pallet Layers**

6 (40ft HQ slip sheet & pallet)

Pallet Product per Layer 16 (slip sheet & pallet)

80 (20ft/40ft slip sheet & pallet) **Total Products per Pallet** 96 (40ft HQ slip sheet & pallet) Container Load. 20-Foot 800 sets (Slip Sheet and Pallet) Container Load, 40-Foot 1680 sets (Slip Sheet and Pallet) Container Load, 40-Foot HighQ 2016 sets (Slip Sheet and Pallet)

What's in the box? AC power cord (1.83m) 5.9ft

HDMI 1.4 cable (1.8m) 5.9 ft

DisplayPort™ 1.2 cable (1.8m, NA/ LA/ Japan/ EMEA AF sku only)

Quick Setup Poster

Warrantv

User Guide and User Guide Languages

Warranty Languages

Arabic, Bahasa Indonesia, Bulgarian, Chinese-S, Chinese-T, Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Hebrew, Hungarian, Italian,

Japanese, Kazakh, Korean, Latvian, Lithuanian, Norwegian, Polish, Portuguese (Brazilian), Portuguese (Iberian), Romanian, Russian, Serbian, Slovak, Slovenian,

Spanish, Swedish, Thai, Turkey, Ukrainian

Warranty Languages English US (EN), English AP (EN-AP), English LA (EN-LA),

> English UK (EN-GB), Arabic (AR) -17x, Bahasa Indonesia (ID), Bosnian (BS), Bulgarian (BG), Chinese-S (CN),

Technical Specifications

Chinese-T (TW), Croatian (HR), Czech (CS), Danish (DA), Dutch (NL), Estonian (ET), Finnish (FI), French Canadian (FC), French European (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JA), Kazakh (KK), Korean (KO), Latvian (LV), Lithuanian (LT), Norwegian (NO), Polish (PL), Portuguese, Brazilian (BR), Portuguese, Iberian (PT), Romanian (RO), Russian (RU), Serbian (SR), Slovak (SK), Slovenian (SL), Spanish, Castilian (ES-ES), Spanish, Latin America (ES-MX), Swedish (SV), Thai (TH) Turkish (TR), Ukrainian (UK), Vietnamese (VI)



Technical Specifications

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.



Summary

| Change Log | | | | |
|-------------------|----------|---------|---|--|
| | | | | |
| December 17, 2024 | V1 to V2 | Updated | HP Client Management Script Library (CMSL) Footnote | |
| | V2 to V3 | | | |
| | V3 to V4 | | | |
| | | | | |
| | | | | |
| | | | | |

